Fixture Type:

Catalog Number:

Project:

Location:

WAC LIGHTING

Twist-N-Lite

Mini Flush Mount

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
❍ FM-240103	❍ CS 2700K/3000K/3500K/4000K/5000K - 90	12W	900	❍ BK Black ❍ BN Brushed Nickel ❍ WT White

Example: **FM-240103-CS-BK**




DESCRIPTION

Quick and convenient. Easy to use and easy to install, our new Twist-N-Lite system offers a variety of surface mounts and pendant luminaires in five color temperatures and three finishes. A single flexible mounting base accommodates our complete suite of Twist-N-Lite products. The flexible design enables you to interchange the fixtures in the field to meet your various lighting applications. This energy-efficient engineering wonder offers dimmable options for high performance and a classic, minimalistic aesthetic. Select your color temperature, Twist it in and Turn it on. Elevating multifunctional illumination to a higher standard.

FEATURES

• Mount and power any fixture in the Twist-N-Lite family by twisting it onto the canopy
• All wiring and connections are made in the junction box prior to installing the mounting base and canopy
• Shared canopy allows for easily swapping between fixtures without adjusting the mounting hardware
• 5-CCT Switchable between 2700K and 5000K
• 45 deg beam angle
• Driver concealed within the fixture
• 5 year warranty

FINISHES:



Black | Brushed Nickel | White

SPECIFICATIONS

Construction	Aluminum with TIR Lens
Power:	12W
Input:	120 VAC,50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	TIR Lens
Rated Life:	50,000 Hours
Mounting:	Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: Electroplated Brushed Nickel, White, Black
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, ADA, Title 24 JA8 Compliant

LINE DRAWING

